

Analog Circuitry Analysis of the STBC02

Li-Ion Linear Battery Charger with LDO, Load Switches and Reset Generator.

IMPORTANT NOTICE REGARDING THE USE OF THIS REPORT:

This report is protected by copyright and may not be by way of trade or otherwise, be copied, reproduced, re-sold, lent, hired out in any form without express written permission from Shanghai Industrial μ Technology Research Institute (hereinafter referred to as SITRI).

SITRI always endeavors to provide accurate and reliable information to its customers. However, it is not possible to guarantee absolute accuracy of all information contained herein and SITRI can assume no liability for inadvertent errors in this report.

This report was prepared for our Clients' private study, analysis or research and for no other purpose. The information contained in this report may describe technical innovations, which are the subject of patents held by third parties. The disclosure by SITRI of any such information is in no form whatsoever an inducement to infringe any patent. SITRI assumes no liability for patent infringement arising from the use of the information contained in this report.

Report #: 11704C0200
Apr. 10, 2017

Contents

DEVICE INFORMATION	II
1.0 INTRODUCTION	1
1.1 DEVICE PARAMETER DEFINITION.....	2
2.0 ARCHITECTURAL OVERVIEW	4
2.1 PACKAGE OVERVIEW.....	4
2.2 PHYSICAL DIE OVERVIEW.....	4
2.3 FUNCTIONAL DIE OVERVIEW.....	8
3.0 SCHEMATIC OF LI-LON LINEAR BATTERY CHARGER WITH LDO, LOAD SWITCHES AND RESET GENERATOR	10
3.1 IN_SYS_CIRCUIT AND RELATED PROTECTION CIRCUITS.....	11
3.2 BATTERY CHARGER.....	11
3.3 LDO AND LDO CURRENT LIMITATION.....	11
3.4 BATTERY_TEMPERATURE_MONITOR.....	11
3.5 THERMAL SENSE.....	12
3.6 DETECTORS.....	12
3.7 SPDTS.....	12
4.0 MAJOR FINDINGS	102
5.0 STANDARD CELL	103